




SS (SUPER-SLIM) SERIES

THIS COMPACT SYSTEM IS EASY-TO-INSTALL WITHOUT ALTERING DUCTWORK AND IS ECONOMICAL TO OPERATE. INSTALLS IN RETURN AIR DUCT AT ANY ANGLE.

FEATURES

- Four sizes.
- Single narrow cell.
- Pre-filter.
- Built-in air flow monitor switch.
- Efficiency 30 to 50% per ASHRAE 52-1 Initial ATM dust spot at rated CFM.
- No major duct modification or wiring required (all hardware included).
- Snap-in solid state power supply. Mounts remotely with 6' cord.
- Operating indicator light.
- ON/OFF switch.
- Baked enamel finish.
- Charcoal filter not available.
- U.L. listed and C.S.A. certified.



SPECIFICATIONS

Type Number	Model Number	CFM Range	A/C Tonnage	BTU Input Range	Power Requirements	Cabinet Dim.			Shipping Weight
						H	W	D	
SS-1620	8C11Y-410	600-1000	1.5 to 2.5	60,000 to 100,000	120 VAC	16"	20"	2 ¹³ / ₁₆ "	22 lbs.
SS-1624	12C11Y-410	1000-1200	2.5 to 3.0	100,000 to 120,000	120 VAC	16"	24"	2 ¹³ / ₁₆ "	24 lbs.
SS-2020	14C11Y-410	1200-1400	3.0 to 3.5	120,000 to 140,000	120 VAC	20"	20"	2 ¹³ / ₁₆ "	26 lbs.
SS-2024	16C11Y-410	1400-1600	3.5 to 4.0	140,000 to 160,000	120 VAC	20"	24"	2 ¹³ / ₁₆ "	28 lbs.